

For Comap manifolds. Features:

- Made of galvanised sheet steel in closed version
- Cabinet height adjustable from 750 to 850 mm
- Cabinet depth 110 - 165 mm
- Powder coating (commercial white RAL 9016)
- With a 45° bent edge
- Supply and return flow connections optionally from left, right or below
- Manifold mounting rail
- Front flap with lock
- Clip rail for control module bar
- Pipe diverting rail
- Packed in a box
- Particularly easy to assemble thanks to detachable front skirt



Classification General Data

Etim Group	Distributors
Etim Class	Frame and door for group distributor housing
Product Name	
Brand	COMAP
Product Type	Exclusive cabinet
Order Code	F18558
GTIN	04013852249592

Attributes

Frame material	Steel
Surface protection frame	Galvanised
Colour frame	White
RAL-number frame	9016
Material door	Steel
Material door	Steel
Surface protection door	Galvanised
Colour door	White
RAL-number door	9016
Type of locking	Key
Width	700 Millimetre
Height	750 Millimetre
Depth	110 Millimetre

Find more information online:

[Folder Surface Heating and Cooling](#)

[Леток за подно греење и ладење](#)

[Brochure Surface Heating and Cooling](#)

[брошура за подно греење и ладење](#)

Fort Blauwkapel 1
1358 DB, Almere - nl

T +31 20 210 34 97
E nl.info@aalberts-hfc.com
I comap.aalberts-hfc.com/nl