



The Comap range includes several distributor models:

- One-pipe or two-pipe.
- With or without isolation.
- The only universal distributor with adjustable ports: the UniverSar 638 distributor, an all-in-one unit to meet water distribution challenges on the job-site.
- All Comap distributors are made in France, at the Comap factory in Abbeville, in the Somme department.

**Advantages**

- A wide range, to meet a wide variety of configuration needs.
- Radiator may be disconnected without draining, with models with isolation valves on the return line.
- Distributor-pipe mechanical coupling included.

This range includes the UniverSar 638 universal distributor, which is available in two versions, for one-pipe and two-pipe systems. Its main strengths:

- With isolation and memory.
- Port can be adjusted 180° for floor or wall connections.
- Bypass function, for when the radiator is not yet installed.
- The centre-to-centre measurement varies depending on the chosen version (renovation or non-renovation).
- Fitting included to connect the pipe to the valve.

**Technical Specifications**

- Comap single pipe and dualpipe and distributors are suited for the following application: heating.  
Nominal pressure: 10 bar.  
Maximum temperature: 110 °C.



Description	Distributor 2-pipe straight M22-1/2" double o-ring with isolation & memory
Order Code	438922B
GTIN	03430650201392
Model	<u>Dual pipe distributors</u>
Connection radiator ["]	1/2" *
Connection tube	M22
Axial distance [mm]	35

\* double o-ring sealing



### Classification General Data

<b>Etim Group</b>	Fittings, flanges and connectors
<b>Etim Class</b>	One-point bottom connecting block
<b>Product Name</b>	915JT Distributor 2-pipe straight M22-1/2
<b>Brand</b>	COMAP
<b>Product Type</b>	M22X1/2"
<b>Order Code</b>	438922B
<b>GTIN</b>	03430650201392

### Attributes

<b>Material</b>	Brass
<b>Suitable for radiator connection 3/4 inch outer</b>	No
<b>Suitable for radiator connection 1/2 inch inner</b>	No
<b>Supply on control side</b>	No
<b>Suitable for two pipe system</b>	Yes
<b>Suitable for single pipe system</b>	No
<b>With presetting</b>	No
<b>Surface protection</b>	Nickel-plated
<b>Lockable</b>	No
<b>Adjustable</b>	No
<b>Thermostatically prepared</b>	No
<b>Kv value</b>	0.19 - 1.82
<b>With dust cap</b>	No
<b>Centre distance, supply/return</b>	35 Millimetre

Fort Blauwkapel 1  
1358 DB, Almere - nl

T +31 20 210 34 97  
E [nl.info@aalberts-hfc.com](mailto:nl.info@aalberts-hfc.com)  
I [comap.aalberts-hfc.com/nl](http://comap.aalberts-hfc.com/nl)