



|                                |                                                       |
|--------------------------------|-------------------------------------------------------|
| Description                    | Thermostatic 4-way valve M22-1/2" - horizontal supply |
| Order Code                     | 920022                                                |
| GTIN                           | 03430650065963                                        |
| Model                          | <u>Thermostatic dual pipe 4-way valves</u>            |
| Connection radioar             | 1/2"                                                  |
| Connection pipe                | M22                                                   |
| Connection head                | M28 x 1,5                                             |
| Axial distance (mm)            | 35                                                    |
| Kv (m <sup>3</sup> /h à BP 2k) | 0,55                                                  |



**Classification General Data**

|              |                                      |
|--------------|--------------------------------------|
| Etim Group   | Fittings, flanges and connectors     |
| Etim Class   | One-point bottom connecting block    |
| Product Name | 920E Thermostatic 4way valve M22-1/2 |
| Brand        | COMAP                                |
| Product Type | e-Senso                              |
| Order Code   | 920022                               |
| GTIN         | 03430650065963                       |

**Attributes**

|                                                 |               |
|-------------------------------------------------|---------------|
| Material                                        | Brass         |
| Suitable for radiator connection 3/4 inch outer | No            |
| Suitable for radiator connection 1/2 inch inner | No            |
| Size of radiator connection                     | 1/2 inch (15) |
| Supply on control side                          | No            |
| Suitable for two pipe system                    | Yes           |
| Suitable for single pipe system                 | No            |
| With presetting                                 | No            |
| Surface protection                              | Nickel-plated |
| Lockable                                        | No            |
| Adjustable                                      | No            |
| Thermostatically prepared                       | No            |
| Kvs value                                       | 2             |
| With dust cap                                   | No            |
| Centre distance, supply/return                  | 35 Millimetre |

Fort Blauwkapel 1  
1358 DB, Almere - nl

T +31 20 210 34 97  
E [nl.info@aalberts-hfc.com](mailto:nl.info@aalberts-hfc.com)  
I [comap.aalberts-hfc.com/nl](http://comap.aalberts-hfc.com/nl)